

Pressure Tester for Diesel PCSm-40 PLUS

Product Code: 910 150 00

Availability: In Stock

Short Description

Art. 910 150 00

5 glow plug adaptors in set

Description

A pressure gauge for compression pressure for Diesel engines
PCSm - 40PLUS

The measuring adapters are screwed in place of glow plugs.

0 - 40 bar (0 - 4.0 MPa)

- Pressure gauge with a pressure hose,
check valve and drain valve 910 300 00

Other Adapters for Diesel engines - see page 9-17 in the HP Catalog.

- Adapters (measuring tips) in place of glow plugs 5 pcs:

2 S (912 450 02) - All older cars without Japanese:

Opel, Peugeot, DB, VW, Ford, Seat, Fiat, Renault, Citroen,
Land Rover, Alfa 145, 146, 155, 164

8 S (912 450 08) - VW, Audi, Seat, Skoda 1.9 / 2.5 TDI, BMW 1.8 /

2.5 TDS2.0 / 3.0 d (00-), Alfa 2.5 TD (95-98), Chrysler 2.5 TD (95-),

Citroen / Peugeot 1.5 / 1.8 / 1.9, Dacia 1.5 dCi (05-), Fiat 1.9 (DW8),

Ford 1.9 TDI, 2.5 TD (Scorpio), Ford, Honda Accord 2.0, Land Rover

2.0 (98-), 2.5Td5 (99-), Mitsubishi 1.9, Nissan 1.5 / 1.9 / 2.2 D / dCi, Opel,

Renault 1.5 / 1.9 / 2.1 / 2.2 DTI (94-), Rover, Volvo 1.9 / 2.5.

6 S (912 450 06) - Audi, Opel, Seat, Ford 2.7, Hyundai, Kia, Mazda,

Mitsubishi, Nissan, Suzuki 2.0, Toyota Hiace, Land Cruiser 2.5., Isuzu 1.5, 2.0, 2.2, 2.4 D / TD, Mazda 2.0, 2.2, 2.5 D / TD, Mitsubishi Pajero 3.2 (03-), Opel 1.7 (TC4EE1), 2.2 (C223), VW Taro 2.4D (89-98)

36 S (912 450 36) - Fiat 1.3 JTD, Opel 1.3 D (Z13DT), Opel Corsa 1.3 CDTI, Lancia Y (03-), Citroen / Peugeot 1.4, 1.6 HDI (05-), Ford 1.4, 1.6 TDCi (04-), Suzuki 1,3 DDiS (03-), Mini D 1.6 (07-)

49 S (912 450 49) - Alfa Romeo 147, 156, 159, 166, Brera, Spider engines 1.9, 2.4 JTD Multijet (03-), Fiat Brava 1.9 D Mutijet (07-), Croma 1.9, 2.4 Multijet (05-), Stilo 1.9 JTD, Multijet engines, 192A5, 937 A5 (04-), Lancia Thesis 2.4 JTD engine .841G000 (03-), Opel Astra H, Signum, Vectra C, Zafira 1.9 CDTI engines: Z 19DT and Z 19 DTH (04-), Saab 9-3 1.9 With 19DT and Z19DTH (04-)

91015000

Art. 91015000

91015000

diesel compression tester

compression tester